

FURUTECH

PURE TRANSMISSION

AEx

オーディオ銘機賞
Audio Excellence Award 2008



High End Performance short and long binding post series

FP-800B(G) FP-800B(R)

FP-805B(G)FP-805B(R)



Features:

- α (Alpha) Phosphor bronze Conductor
- Eutectic Copper Alloy Housing
- Nylon (red, white) and Polycarbonate(clear) insulation
- Connections: Soldered or Set-screw
- Specified for core diameters up to 4.5mm



FP-800 B 24k Gold or Rhodium Plated Non-magnetic Conductor

High End Performance short Binding post (2pcs/set)

Dimensions: Housing---15.6± 0.1mm diameter X22mm± 0.1mm,

Insulation--- Polycarbonate (Clear) 19.3± 0.1mm diameter X7.3mm± 0.1mm ,49.7 mm± 0.1mm overall length.

FP-805 B 24k Gold or Rhodium Plated Non-magnetic Conductor


High End Performance long Binding post (2pcs/set)

Dimensions: Housing---15.6± 0.1mm diameter X22mm± 0.1mm,

Insulation--- Polycarbonate (Clear) 19.3± 0.1mm diameter X7.3mm± 0.1mm ,70.1 mm± 0.1mm overall length.

Panel Cut-out Size
for FP-800/805

FOR FRONT
MOUNTING USE



Remark : B=Black Painted Housing, (G)=24k Gold Plated

All metallic parts are treated with the

**FURUTECH α (Alpha) Process (Super Cryogenic & Demagnetizing Treatment.)*

FURUTECH CO.,LTD. service@furutech.com

Make A More Powerful Connection with Furutech!